

<b>MODEL</b>	EW-1505
<b>MECHANICAL SPECIFICATIONS</b>	
Overall diameter (mm)	389
Bolt circle diameter (mm)	370
Baffle cutout diameter (mm)	350
Depth (mm)	154
Net weight (kg)	5.3
Shipping box (single carton box) (mm)	
<b>ELECTRICAL SPECIFICATIONS</b>	
Nominal diameter (inch)	15
Nominal impedance ( $\Omega$ )	8
DC resistance ( $\Omega$ )	5.5
Nominal power handling (W)	300
Program power (W)	600
Sensitivity (1W/1m) (dB)	97
Frequency range (Hz)	40-3000
Voice coil diameter (mm)	66.5
Voice coil material	Cu
Former material	Aluminium
Magnetic gap depth (mm)	10
Magnetic(Oz)	53.2
Flux density (磁通密度) T	1.2
<b>THIELE &amp; SMALL PARAMETERS</b>	
Fs (Hz)	33
Re ( $\Omega$ )	5.5
Qes	0.4
Qms	2.63
Qts	0.35
Vas (L)	332
Sd (cm <sup>2</sup> )	855
Xmax (mm)	3
Mms (gr)	74.35
Bl (N/A)	14.4
Le@1K (mH)	1.69
Mmd (gr)	60.22
Cms (mm/N)	0.33
Rms (kg/s)	5.75

(\*)2 hours in free air according to AES2-1984(r2003)

(\*)1 inch=25.4mm

