

## PRESSURE SWITCH TYPE XP600

**Hot Water, Steam, Neutral Liquids,  
Light Oils, Air, Inert Gases**

Wetted Materials	Brass Silicone (Membrane)
Main Body	Technopolymer (PET)
Ambient Temperature	-10 ~ +50 °C
Media Temperature	-10 ~ +125 °C
Burst Pressure	>20 Bar
Electrical	SPDT 10(2) - 250 VAC <sup>μ</sup> SPST NO/NC 10(2) - 250 VAC <sup>μ</sup>
Electrical Connection	Terminal 6.3 x 0.8
Thermal Drift	0.04 bar / 10 °C to datum 20 °C
Protection	IP45 with Cap A0158100.020



*Ideal for Hot Water, Steam and  
semi-aggressive media*

Pressure Connection	Part Number	Adjustable Pressure Range	Fixed Differential	Electrical Data	Weight
Inches		Bar	Bar		gm
G <sup>1</sup> / <sub>8</sub> M	<b>XP73AE61.000</b>	0.2—1.2	0.30 ± 0.15	10 A x 250 V	80
G <sup>1</sup> / <sub>8</sub> M	<b>XP73CE61.000</b>	1.0—2.5	0.30 ± 0.15	10 A x 250 V	80
G <sup>1</sup> / <sub>8</sub> M	<b>XP73DE61.000</b>	1.5—4.0	0.35 ± 0.15	10 A x 250 V	80
G <sup>1</sup> / <sub>8</sub> M	<b>XP73EE61.000</b>	2.0—6.0	0.35 ± 0.20	10 A x 250 V	80

	<p>Homologations</p> <p>EN60730-1 EN60730-2-6</p>	<p>Electrical Connections</p>
--	---	-------------------------------

### Options

Connections	G <sup>1</sup> / <sub>4</sub> M & ¼ NPT Male
Pressurised Body	Stainless Steel
IP54 Protection Cap	A0158100.020