

SIM300D

GSM/GPRS Module



The SIM300D is a complete Tri-band GSM/GPRS solution in a SMT module which can be embedded in the customer application.

Featuring an industry-standard interface, the SIM300D delivers GSM/GPRS 900/1800/1900MHz performance for voice, SMS, Data, and Fax in a small form factor and with low power consumption. With a tiny configuration of 33mm x 33mm x 3 mm, SIM300D can fit almost all the space requirements in your industrial applications, such as M2M, Telematics and other mobile data communication systems.

- Tri- band GSM/GPRS module with a size of 33mmx33mmx3mm
- SMT type suit for customer application
- An embedded Powerful TCP/IP protocol stack
- Based upon mature and field-proven platform, backed up by our support service, from definition to design and production

We make future wireless

General features

- Tri-Band GSM/GPRS 900/1800/1900MHz
- GPRS multi-slot class 10/8
- GPRS mobile station class B
- Compliant to GSM phase 2/2+
 - Class 4 (2 W @900 MHz)
 - Class 1 (1 W @ 1800/1900MHz)
- Dimensions: 33* 33 * 3 mm
- Weight: 7.8 g
- Control via AT commands (GSM 07.07 ,07.05 and SIMCOM enhanced AT Commands)
- SIM application toolkit
- Supply voltage range 3.4 ... 4.5 V
- Low power consumption
- Normal operation temperature: -20 °C to +55 °C
- Restricted operation temperature: -30°C to -20°C and +55°C to +80°C
- Storage temperature -40 °C to +85 °C

Specifications for fax

- Group 3, class 1

Specifications for data

- GPRS class 10: max. 85.6 kbps (downlink)
- PBCCH support
- Coding schemes CS 1, 2, 3, 4
- CSD up to 14.4 kbps
- USSD
- Non transparent mode
- PPP-stack

Specifications for SMS via GSM / GPRS

- Point-to-point MO and MT
- SMS cell broadcast
- Text and PDU mode

Drivers

- MUX Driver

Specifications for voice

- Tricodec
 - Half rate (HR)
 - Full rate (FR)
 - Enhanced Full rate (EFR)
- Hands-free operation (Echo suppression)

Interfaces

- Interface to external SIM 3V/ 1.8V
- Two analog audio interfaces
- RTC backup
- SPI interface
- Serial interface and debug interface
- Antenna pad
- Charge interface
- GPIO

Compatibility

- AT cellular command interface

Approvals

- FTA

Attachment (pin assignment)

