



# NC-SC1400 *Brief Datasheet*

## Nickel Cadmium Battery

### 1 Dimension





### 3 Electrical Characteristics



### 2 Basic Specification

Nominal Voltage		1.2V	
Nominal Capacity*	Typical	1450mAh (0.2C discharge)	
	Minimum	1400mAh (0.2C discharge)	
Charge	Standard	140mA for 16hrs	
	Fast	1400mA for Approx.75mins	
Internal Impedance		$\leq 20\text{mohms}$	
Life Cycles		500 cycles	
Operation Temperature	Charge	Standard	$0^{\circ}\text{C}$ to $40^{\circ}\text{C}$
		Fast	$10^{\circ}\text{C}$ to $40^{\circ}\text{C}$
	Discharge		$-10^{\circ}\text{C}$ to $50^{\circ}\text{C}$
	Storage	<1year	$-10^{\circ}\text{C}$ to $30^{\circ}\text{C}$
<3month		$-10^{\circ}\text{C}$ to $40^{\circ}\text{C}$	
Discharge cut-off voltage		1.0V	
Weight		Approx.42g	



Note:\*Typical values relative to cells stored for less than 3 months or less at  $30^{\circ}\text{C}$  max.

\*After charging at 0.1C for 16 hours.

\*We recommend cells or batteries are charged once every 3 months.

Note: Any representations in this brochure concerning performance, are for informational purposes only and are not construed as warranties either expressed or implied, of future performance.