




Single secondary version
 Primary: pins 1 - 8
 Secondary: pins 10 - 15



Double secondary version
 Primary: pins 1 - 8
 Secondary 1: pins 9 - 10
 Secondary 2: pins 15 - 16



MAIN FEATURES

- Unitary insulation test at **5KV**
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** (130°C)
- Protection index: **IP00**
- Weight: **900gr**
- **Other voltages or pin-out under request**

JESIVA Part nº	RATED POWER	PRIMARY	SECONDARY	TEMP	Recommended FUSE
E6630.35.1.06	35VA	230V	6V / 5.83A	40°C/B	Prim.200mA/T
E6630.35.1.07	35VA	230V	7.5V / 4.66A	40°C/B	Prim.200mA/T
E6630.35.1.09	35VA	230V	9V / 3.88A	40°C/B	Prim.200mA/T
E6630.35.1.12	35VA	230V	12V / 2.91A	40°C/B	Prim.200mA/T
E6630.35.1.15	35VA	230V	15V / 2.33A	40°C/B	Prim.200mA/T
E6630.35.1.18	35VA	230V	18V / 1.94A	40°C/B	Prim.200mA/T
E6630.35.1.24	35VA	230V	24V / 1.45A	40°C/B	Prim.200mA/T
E6630.35.2.06	35VA	230V	2x6V / 2x2.91A	40°C/B	Sec.2x3.15A/F
E6630.35.2.07	35VA	230V	2x7.5V / 2x2.33A	40°C/B	Sec.2x2.5A/F
E6630.35.2.09	35VA	230V	2x9V / 2x1.94A	40°C/B	Sec.2x2A/F
E6630.35.2.12	35VA	230V	2x12V / 2x1.45A	40°C/B	Sec.2x1.6A/F
E6630.35.2.15	35VA	230V	2x15V / 2x1.16A	40°C/B	Sec.2x1.25A/F
E6630.35.2.18	35VA	230V	2x18V / 2x0.97A	40°C/B	Sec.2x1/F
E6630.35.2.24*	35VA	230V	2x24V / 2x0.73A	40°C/B	Sec.2x0.8A/F

DATA SHEET

EI66/30

Encapsulated transformer

JESIVA 
transformers

Code:

E6630.35.X.XX

Date:

Dec 2011

www.JESIVA.com