



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26									
/CS1	/RES	AO	R/W	E	DD	D1	D2	D3	D4	D5	D6	D7	VDD	VSS	VO	UT	PC	3	PC	4	PC	1	-	CA	PC	2	PC	2	-	V1	V2	V3	V4	V5

VDD :
 DISPLAY TYPE :
 POLARIZER MODE :
 CONNECTOR :
 VIEW ANGLE :
 DRIVING METHOD :
 DISPLAY DRIVER :
 BACKLIGHT COLOR :
 BACKLIGHT VF :
 BACKLIGHT If :
 BEZEL FINISH :
 OPERATING TEMP :
 STORAGE TEMP :

3.0V \pm 5%
 FSTN, POSITIVE MODE
 TRANSPARENT
 PINS
 6 O'CLOCK
 9.0V, 1/65 DUTY, 1/9 BIAS
 NT7532
 WHITE
 3.2V \pm 0.2V
 120mA TYP
 NIL
 -20°C TO +70°C
 -30°C TO +80°C

DRAWN BY : F T T 2005-04-18
 CHECKED BY :
 Approve By :

海南清华显示器件技术开发有限公司
 HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

COG12864-34-FP-FB-W-LG-W

REV:	A1
SIZE:	A4
SHEET:	1 OF 1
SCALE:	NTS

UNITS: MM
 TITL: CUSTOMER LCD